

PRINTER

Intermec® 6808

Features:

- Economical, yet highly functional
- Lightweight, belt-clip design makes it easy to carry
- Rugged housing built for the field environment
- 4" (10.2 cm) paper width capability
- 40-column format, with optional compressed 80-column capability
- Compatible with the Intermec® 6804T, 6805a and 6806 printers
- Linerless label option



Economical Yet Functional

The Intermec® 6808 thermal printer is the newest addition to the Intermec line of belt-clip printers. It is small, lightweight, durable and weather resistant, so it is easily incorporated into field use. Its reliable printer mechanism offers exceptional print clarity with the versatility of printing graphics, bar codes and logos. It can quickly print both standard and bar-coded receipts, yet provides users with a 4-inch paper width capability to accommodate 40-column formats.



80-column Alternative

The unit offers the ability to provide a compressed 80-column receipt, without the field worker having to carry the bulk of a larger 80-column printer.



The rotating belt-clip design makes mobility convenient for users.

Long-Lasting Power Supply

The Intermec 6808 has a vehicle charger option that ensures a long day's work in the field. It has a sleep mode for battery conservation, and the unit wakes itself up when it senses data input.

Easy to Use

The Intermec 6808 is fully compatible with the Intermec 6804T, 6805a and 6806 printers. In addition, its functional design makes paper loading simple, since roll-type paper fits easily into place. And its one-year warranty provides additional peace of mind.



SPECIFICATIONS

Intermec® 6808



Physical Characteristics

Length: 16.5cm (6.5")
Width: 16.9cm (6.7")
Depth: 6.7cm (2.6")
Weight: With one battery 580g (20.6oz)

Environment

Operating Temperature:
14° to 140° F (-10° to 60°C)
Drop Spec: Withstands multiple 183cm (6') drops to concrete

Power Source

Internal battery, Lilon 1.8 amp/hr, 7.2v, 1350mAH
User replaceable

Battery Recharging

Nine hours to full charge using a vehicle cigarette lighter power adapter or standard AC power adapter

Printer Mechanism

Characteristics:
Direct thermal line printer
203 dots per inch (dpi)
Print Speed: 5.1cm (2") per second

Fonts

Three resident fonts
Up to four additional fonts may be downloaded

Print Capabilities

Characters, graphics and bar codes

Print Medium

Thermal paper, one ply
Paper Width: 11.2cm (4.4")

Print Duration Per Charge

Over 9144cm (3,600")

Interface

IrDA®
RS-232 serial

Chargers

AC wall charger
12V vehicle charger

Agency Approvals

FCC Title 47, Part 15, Subpart B, Class B
EN 55022 Class B
EN 50082-1
EN 60950

Warranty

One year warranty. Additional service packages available.

Note

Some approvals and features may vary by country and may change without notice. Specs may vary based upon the specific configuration or features selected. Please check with your local Intermec sales office for further information.

North America • Intermec Technologies Corporation • Systems & Solutions • 550 2nd Street S.E. • Cedar Rapids, Iowa 52401 • 1 (800) 452-2757 tel • 1 (319) 369-3453 fax • **Accessories:** 1 (800) 255-6292 tel • 1 (319) 369-3625 fax • **Label Products:** 1 (800) 227-9947 tel • 1 (513) 874-8487 fax • **Amtech Systems Division** • 19111 Dallas Parkway, Suite 300 • Dallas, TX 75287-3106 • (800) 923-4824 tel • (972) 733-6699 fax

Europe/Middle East/Africa • Sovereign House • Vastern Road • Reading RG1 8BT Berkshire • United Kingdom • +44 118 987 9400 tel • +44 118 987 9401 fax • Label Products: +31 24 3723 100 tel • +31 24 3780 070 fax

Asia Pacific/Latin America • 6001 36th Avenue West • P.O. Box 4280 • Everett, Washington 98203-9280 • 1 (800) 347-2636 tel • 1 (319) 369-3324 fax • Label Products: 1 (800) 227-9947 tel • 1 (513) 874-8487 fax

World-Wide Fax Document Retrieval Service • 1 (650) 556-8447 tel • 1 (800) 755-5505 (North America Only)

Internet • www.intermec.com **E-mail** • info@norand.com

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice. Copyright © 2000 Intermec Technologies Corporation. All rights reserved. Intermec® is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in U.S.A. #960-701-052 (01/00)